

# Gemini<sup>®</sup> Fluoro Wetting Levelling Surfactant

## BH-15W

### Introduction:

BH-15W is a economical low budget nonionic wetting leveling surfactant designed especially for waterborne paints、inks and adhesives etc. It is APEO free and can minimize liquid surface tension that has excellent anti-cratering performance in waterborne system. It is outstanding for pigment wetting, enable better color development.

### Typical Properties:

Ingredient	Perfluoroalkyl Polyoxyethylene Ether
Appearance	Amber liquid
Solid Content	10%
Solvent	90%
PH	11-12 (0.1% wt in water)
Density	1.0 (25°C g/ml)
Surface Tension	(25°C, 0.1% wt water solution, Surface Tension < 19 dyne/cm)
Solubility	Soluble in water and polar organic solvents

### Application:


Suggested use rates are 0.5~1% wt solid, make adjustment according to your own recipe

Widely application in emulsion paint、wood lacquer、metal anti-corrosion paint、plastic lacquer etc.

### Attentions:

- . During processing, wear protection clothes, be careful of eye、skin contact.
- . Keep the container sealed and store in cool、well ventilated locations.
- . It will have sediments and layering in low temperature, no worries, please warm up with 40°C hot water and mix well before use.

**Packaging/Transport:** 25Kg plastic jug. Not classified as dangerous in the meaning of transport regulations.



[www.weissbonya.com](http://www.weissbonya.com)

Hunan Weiss Bonya Co., Ltd

Email: [Weissbonya@gmail.com](mailto:Weissbonya@gmail.com)